

## CLAIMS

What is claimed as being new and desired to be protected by LETTERS PATENT of the United States is as follows:

1. A belt-worn article carrier apparatus, comprising:

an elastic cord assembly which includes a first cord end, a second cord end, and an intermediate cord portion between said first cord end and said second cord end,

a waist belt assembly which includes an adjustable belt portion, a first buckle portion attached to a first end of said adjustable belt portion, a second buckle portion attached to a second end of said adjustable belt portion, and a cord-reception wall attached to said adjustable belt portion, wherein said cord-reception wall and said adjustable belt portion define a cord-reception channel,

first article attachment means for attaching a first article to said first cord end, and

second article attachment means for attaching a second article to said second cord end.

2. The apparatus of claim 1 wherein said adjustable belt portion includes:

a first adjustable belt portion located at a first end of said adjustable belt portion, and

a second adjustable belt portion located at a second end of said adjustable belt portion.

3. The apparatus of claim 1 wherein said elastic cord assembly further includes:

a cord adjustment loop in said intermediate cord portion, and  
a cord adjustment lock attached to said cord adjustment loop.

4. The apparatus of claim 3 wherein said cord adjustment lock includes:  
a clamping spring for clamping said cord adjustment loop, and  
a clamp release button for releasing clamping action of said clamping spring on said cord adjustment loop.

5. The apparatus of claim 1 wherein said elastic cord assembly further includes:

said first article attachment means connected to said first cord end,  
and  
said second article attachment means connected to said second cord end.

6. The apparatus of claim 5 wherein said first article attachment means and said second article attachment means include double-sided hook and loop fastener straps.

7. The apparatus of claim 6 wherein each of said double-sided hook and loop fastener straps includes hooks on one strap side and loops on the opposite strap side.

8. The apparatus of claim 1 wherein:  
the first article is a first antler, and  
the second article is a second antler.

9. The apparatus of claim 1 wherein:  
said first article attachment means include a first article attachment loop, and  
said second article attachment means include a second article attachment loop.

10. The apparatus of claim 1 wherein said cord-reception wall includes first grommets which receive said first cord end and said second cord end.

11. The apparatus of claim 1, further including:  
an auxiliary elastic cord assembly which includes a first auxiliary cord end, a second auxiliary cord end, and an intermediate auxiliary cord portion between said first auxiliary cord end and said second auxiliary cord end,  
first auxiliary article attachment means for attaching a third article to said first auxiliary cord end, and

second auxiliary article attachment means for attaching a fourth article to said second auxiliary cord end.

12. The apparatus of claim 11 wherein:

said third article is a first call unit, and

said fourth article is a second call unit.

13. The apparatus of claim 11 wherein:

said first auxiliary article attachment means include a third article attachment loop, and

said second auxiliary article attachment means include a fourth article attachment loop.

14. The apparatus of claim 11 wherein said cord-reception wall includes auxiliary grommets for receiving said first auxiliary cord end and said second auxiliary cord end.